

# FROSTED ARCHITECTURAL SQUARES



## FROSTED ARCHITECTURAL SQUARES

Featuring frosted motifs of architectural forms, Frosted Architectural Squares allows you to effectively customize your windows and glass partitions.



Tintfit Window Films warranty

**5 YEARS** 



Fire-resistance rating





Storage from -5°C to +40°C





REACH RoHS compliant RESPECTED

## TECHNICAL DATASHEET

Data calculated based on film applied to clear glass 3 mm thick (\*on double glazing 4-16-4)

Ultraviolet transmission	NC %
Visible light transmission	- %
Reflection of external visible light	- %
Reflection of internal visible light	- %
Total solar energy rejected	- %
Total solar energy rejected 2	- %
Solar ratio:	
Solar energy reflection	- %
Solar energy absorption	- %
Solar energy transmission	- %
Reduction in Solar Glare	- %
g-value	=-
u-value	3
Shading coefficient	NC
Installation type: Internal application	
Roll length	50 m
PET / PVC composition	PET
Thickness	40 μ

Colour: FROSTED

# CONSTRUCTION

- 1. High optical quality polyester with printed design
- **2.** PS adhesive, glass polymerization within 15 days **3.** Protection release liner, disposable after installation


## INSTALLATION ADVICE

Vertical installation and on standard glass surface\*

Clear single pane	~
Tinted single pane	~
Reflective tinted single pane	~
Clear double pane	~
Tinted double pane	~
Reflective tinted double pane	~
Gas-filled double pane - Low E	<b>~</b>
STADIP EXT. clear double pane	~
STADIP INT. clear double pane	~

✓ Yes Caution X No

\*Recommendations provided on the basis of a glazed surface covering up to 2.5m2.



# MAINTENANCE INSTRUCTIONS

Soapy water solution, do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Non-contractual data, Tintfit Window Films reserves the right to modify the composition of its films at any time.