



### CLEAR PRINT PVC

The Clear Print PVC film can be printed on with any type of printing machine or method, while offering the best visual coefficient.



Tintfit Window Films warranty

**3 YEARS**



Fire-resistance rating

**M1**



Storage from -5°C to +40°C

**3 YEARS**



REACH RoHS compliant

**RESPECTED**

### TECHNICAL DATASHEET


Data calculated based on film applied to clear glass 3 mm thick (\*on double glazing 4-16-4)

Ultraviolet transmission	>30 %
Visible light transmission	91 %
Reflection of external visible light	7 %
Reflection of internal visible light	6 %
Total solar energy rejected	10 %
Total solar energy rejected 2*	11 %
Solar ratio :	
Solar energy reflection	7 %
Solar energy absorption	8 %
Solar energy transmission	85 %
Reduction in Solar Glare	8 %
g-value	0.88
u-value	5.7
Shading coefficient	0.9
Installation type :	
Roll length	50 m
PET / PVC composition	PVC
Thickness	80 µ

Colour : TRANSPARENT

### CONSTRUCTION

1. Transparent polymer PVC
2. Removable polyacrylate solvent adhesive
3. Protection release liner, disposable after installation



### MAINTENANCE INSTRUCTIONS

Soapy water solution, do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

*Non-contractual data, Tintfit Window Films reserves the right to modify the composition of its films at any time.*

### INSTALLATION ADVICE

Vertical installation and on standard glass surface\*\*

Clear single pane	✓
Tinted single pane	✓
Reflective tinted single pane	✓
Clear double pane	✓
Tinted double pane	✓
Reflective tinted double pane	✓
Gas-filled double pane - Low E	✓
STADIP EXT. clear double pane	✓
STADIP INT. clear double pane	✓

✓ Yes    ! Caution    ✗ Not recommended

\*Recommendations provided on the basis of a glazed surface covering up to 2.5m<sup>2</sup>.