



WHITE PRINT PVC

The White Print PVC film can be printed on with any type of printing machine or method. It has a bubble free adhesive guaranteeing the white effect of the film.



Tintfit Window Films warranty

3 YEARS



Storage from -5°C to +40°C

3 YEARS



REACH RoHS compliant

RESPECTED

TECHNICAL DATASHEET


Data calculated based on film applied to clear glass 3 mm thick (*on double glazing 4-16-4)

Ultraviolet transmission	< 30 %
Visible light transmission	91 %
Reflection of external visible light	7 %
Reflection of internal visible light	6 %
Total solar energy rejected	10 %
Total solar energy rejected 2*	11 %
Solar ratio :	
Solar energy reflection	7 %
Solar energy absorption	8 %
Solar energy transmission	85 %
Reduction in Solar Glare	8 %
g-value	0.88
u-value	5.7
Shading coefficient	0.9
Installation type : Internal application + External application	
Roll length	50 m
PET / PVC composition	PVC
Thickness	100 µ

Colour : WHITE

CONSTRUCTION

1. White monomer PVC
2. Removable polyacrylate solvent adhesive
3. Protection release liner, disposable after installation



MAINTENANCE INSTRUCTIONS

Soapy water solution, do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

INSTALLATION ADVICE

Vertical installation and on standard glass surface**

Clear single pane	✓
Tinted single pane	✓
Reflective tinted single pane	✓
Clear double pane	✓
Tinted double pane	✓
Reflective tinted double pane	✓
Gas-filled double pane - Low E	✓
STADIP EXT. clear double pane	✓
STADIP INT. clear double pane	✓

✓ Yes ! Caution ✗ Not recommended

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².