



PREMIUM ULTRA LIGHT 70

Premium Ultra Light 70 tinted automotive window film confers a touch of aesthetic embellishment to any vehicle, whilst ensuring privacy from prying eyes.



Tintfit Window Films warranty

LIFETIME



Storage from -5°C to +40°C

3 YEARS



REACH RoHS compliant

RESPECTED

TECHNICAL DATASHEET


Data calculated based on film applied to clear glass 3 mm thick (*on double glazing 4-16-4)

Ultraviolet transmission	1 %
Visible light transmission	70 %
Reflection of external visible light	7 %
Reflection of internal visible light	8 %
Total solar energy rejected	17 %
Total solar energy rejected 2	17 %
Solar ratio :	
Solar energy reflection	4 %
Solar energy absorption	25 %
Solar energy transmission	78 %
Reduction in Solar Glare	27 %
g-value	0.77
u-value	-
Shading coefficient	
Installation type : Internal application	
Roll length	30,5 m
PET / PVC composition	PET
Thickness	25 µ

Colour : BLACK

CONSTRUCTION

1. "Hard" scratch resistant layer, for durability and ease of maintenance during window cleaning
2. Dyed polyester without optical distortion
3. PS adhesive, glass polymerization within 15 days
4. Protection release liner, disposable after installation



MAINTENANCE INSTRUCTIONS

Soapy water solution, do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Non-contractual data, Tintfit Window Films reserves the right to modify the composition of its films at any time.

INSTALLATION ADVICE

Vertical installation and on standard glass surface*

Clear single pane	✓
Tinted single pane	!
Reflective tinted single pane	✓
Clear double pane	✓
Tinted double pane	!
Reflective tinted double pane	✓
Gas-filled double pane - Low E	!
STADIP EXT. clear double pane	!
STADIP INT. clear double pane	✗

✓ Yes ! Caution ✗ No

These general recommendations are to be complemented by a commitment-free detailed thermal analysis report.