



### OPAL FROST

Opal Frost is designed to provide protection against the scrutiny of prying eyes. Whilst completely opalescent, the film still allows most natural light to pass through.



Tintfit Window Films warranty

**5 YEARS**



Storage from -5°C to +40°C

**3 YEARS**



REACH RoHS compliant

**RESPECTED**

### TECHNICAL DATASHEET


Data calculated based on film applied to clear glass 3 mm thick (\*on double glazing 4-16-4)

Ultraviolet transmission	1 %
Visible light transmission	76 %
Reflection of external visible light	15 %
Reflection of internal visible light	15 %
Total solar energy rejected	18 %
Total solar energy rejected 2	19 %
Solar ratio :	
Solar energy reflection	10 %
Solar energy absorption	17 %
Solar energy transmission	73 %
Reduction in Solar Glare	20 %
g-value	0.77
u-value	5.6
Shading coefficient	NC
Installation type : Internal application	
Roll length	50 m
PET / PVC composition	PVC
Thickness	90 µ

Colour : FROSTED

### CONSTRUCTION

1. 100µ Frosted monomer PVC
2. Half Permanent Adhesive, allowing the "degassing" of the actual surface, and limits the adhesive transfer during removal
3. Protection release liner, disposable after installation



### MAINTENANCE INSTRUCTIONS

Soapy water solution, do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

*Non-contractual data, Tintfit Window Films reserves the right to modify the composition of its films at any time.*

### INSTALLATION ADVICE

Vertical installation and on standard glass surface\*

Clear single pane	✓
Tinted single pane	✓
Reflective tinted single pane	✓
Clear double pane	✓
Tinted double pane	✓
Reflective tinted double pane	✓
Gas-filled double pane - Low E	✓
STADIP EXT. clear double pane	✓
STADIP INT. clear double pane	✓

✓ Yes ! Caution ✗ No

\*Recommendations provided on the basis of a glazed surface covering up to 2.5m<sup>2</sup>.